

Technical Datasheet SW 3 H

- The universal „3 litre unit“ for
- the use in the laboratory for cleaning and degassing
- the cleaning of small mechanic items and tools in the industry



Elektrical Data:

- Mains voltage / Variants: 100-120 / 220-240 (Vac)
- Ultrasonic Frequency: 37 kHz
- Power consumption total: 280 Watt
- Ultrasonic power effective: 80 Watt
- Ultrasonic peak max.: 320 Watt
- Heating power: 200 Watt
- Timer: 1 till 30 min. and ∞
- Temperature range: 30°C-80°C variable in 5°C steps

Mechanical Data:

- Tank max volume (approx. litre): 2.75
- Tank service volume (approx. litre): 1.9
- Tank internal dimensions: 235 x 134 x 97 (W x D x H / approx. mm)
- Unit external dimension: 322 x 175 x 214 (W x D x H / approx. mm)
- Weight (approx. Kg): 3.3
- Material Housing (Stainless steel): V2A 1.4301 (AISI 304)
- Material Tank (Stainless steel): V2A 1.4301 (AISI 304)
- Thickness Tank (approx. mm) 0.7

Technical properties:

- Number of transducer: 1
- Unit handles: 2

Accessories:

- Basket internal dimensions (approx. mm): 191 x 95 x 50
- Basket loading (approx. Kg): 1.0
- Basket (order-no.) 100 400
- Cover: 100 002
- Set: 2 beakers with cover, cover with 2 holes and rubber rings (order-no.) 100 526