

## Technical Datasheet SW 6 H

- larger basket dimensions and a deeper tank than SW3H for long instruments or a larger amount of tools or other cleaning items
- also available with cut-out cover and 1 litre glass beakers
- drain on the back, to be operated on the side



### Elektrical Data:

- Mains voltage / Variants: 100-120 / 220-240 (Vac)
- Ultrasonic Frequency: 37 kHz
- Power consumption total: 550 Watt
- Ultrasonic power effective: 150 Watt
- Ultrasonic peak max. 600 Watt
- Heating power: 400 Watt
- Ultrasonic Intensity (W / cm<sup>2</sup>) 2,6
- Timer: 1 till 30 min. and ∞
- Temperature range: 30°C – 80°C variable in 5°C steps

### Mechanical Data:

- Tank max volume (approx. litre): 5.75
- Tank service volume (approx. litre): 4.3
- Tank internal dimensions: 298 x 150 x 150 (W x D x H / approx. mm)
- Unit external dimension: 380 x 184 x 265 (W x D x H / approx. mm)
- Weight (approx. Kg): 5.1
- Material Housing (Stainless steel): V2A 1.4301 (AISI 304)
- Material Tank (Stainless steel): V2A 1.4301 (AISI 304)
- Thickness Tank (approx. mm) 0.8

### Technical properties:

- Number of transducer: 3
- Unit handles: 2
- Drain Diameter (inch“) 3/8“

### Accessories:

- Basket internal dimensions (approx. mm): 246 x 106 x 75
- Basket loading (approx. Kg): 5.0
- Basket (order-no.) 100 401
- Cover: 100 003