



PRODUCT ADVANTAGES

- Easy-to-use electronic controls with 3 cycles - 60, 90 & 180 seconds
- Electronic temperature gauges
- Suitable for all dish & glass washing applications. Useable chamber height of 440mm. Able to wash 1/1 GN pans when using optional open ended tray racks
- Low 2.3 litres per cycle rinse volume dish / glasswasher with Rinse Pump to guarantee rinse volume, pressure and sanitation results
- Fully enclosed 4 sided hood design - avoiding loss of energy / steam
- Optimum hygienic - deep drawn tank with coved corners (no welds) and SELF-CLEANING CYCLE
- Polypropylene wash and stainless steel rinse arm with patented WIDE ANGLE FAN nozzle to maximise wash & rinse performance
- Wash pump inlet strainer to ensure machine reliability
- Includes chemical dispensers, fill hose, power lead & pump-out drain for quick & easy installation
- Includes 1 x plate rack & 1 x cutlery holder
- WATERMARK approved
- MADE IN GERMANY

TECHNICAL DATA

Wash tank temperature	55 - 65°C
Rinse water temperature (booster tank)	Minimum 82°C
Low tempe cut-out (thermostop) activated	Yes
Cycle times	1. 60sec. 2. 90sec. 3. 180 sec.
Water consumption	2.3 litres
Tank capacity	21 litres
Tank heating	2.5 kW
Power supply	415/50/3
Booster loading	6.2 kW
Total loading	7.1 kW
Pump capacity	0.7 kW
Loading height	440 mm
Bench to bench - internal dimension	628 mm

*Thermostop guarantees required temperatures with cold water, the actual cycle times extend accordingly. For corner operation we recommend to make the right side of the machine accessible for service.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.

DIMENSIONAL DRAWING

CONNECTIONS

① Drain hose	2,000 mm ID 20 / OD 25 Independent gravity waste to tundish
RO-S drain	
② Supply hose	2,000 mm R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 (0.8 with softener)- 6 bar
Max. supply water temperature	60 °C 35 °C With RO
③ Power cord	2,500 mm
Supply hose for	
④ Detergent	2,000 mm
⑤ Rinse aid	2,000 mm

